

Application No. 10/717,825
Atty. Docket No. 20714-0028-U1

B. AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

CLAIMS

1. (Currently Amended). A filter rack for a forced air-circulating system, the filter rack comprising:
 - a plurality of longitudinal members having a first flange flanges adapted to receive and retain a filter, a second flange adapted for mounting into an air handling system, and having channels adapted to receive and retain a connector, each longitudinal member adapted for connection to at least two other longitudinal members to form a rectangular frame; and
 - a plurality of connectors adapted for insertion into corresponding channels of the longitudinal member for connecting each longitudinal member to at least one other longitudinal member;
2. (Original). The filter rack of claim 1, wherein the longitudinal members are comprised of a back member, at least two side members, and a front member.
3. (Currently Amended). The filter rack of claim 2, wherein the front member is configured to provide an opening to permit a filter to pass into the assembled filter rack and to be received and retained by the first flange flanges on the longitudinal members.
4. (Original). The filter rack of claim 3, wherein the longitudinal members are comprised of a corrosion-resistant rigid material.
5. (Original). The filter rack of claim 4, wherein the corrosion-resistant rigid material is selected from the group consisting of: plastic, composites, aluminum, and coated metal.
6. (Original). The filter rack of claim 5, wherein the rigid material is formed by extrusion to produce a longitudinal member having a predetermined cross-sectional profile.
7. (Original). The filter rack of claim 6, wherein the connectors are comprised of picture frame hardware.

Application No. 10/717,825
Atty. Docket No. 20714-0028-U1

8. (Original). The filter rack of claim 6, wherein the connectors are flat L-shaped connectors, and wherein the channel is provided in the rear face of each longitudinal member.
9. (Original). The filter rack of claim 8, wherein the connector further includes at least one fastener.
10. (Original). The filter rack of claim 9, wherein the at least one fastener is selected from the group consisting of bolts, screws, tabs, hook and loop type fasteners, clamps, caulking, clamps, and adhesives.
11. (Original). The filter rack of claim 8, wherein the filter rack is further comprised of a door that is attached to the at least one longitudinal member by removable attachment means.
12. (Original). The filter rack of claim 9, wherein the filter rack is further comprised of a door that is attached to at least two longitudinal members by removable attachment means.
13. (Original). The filter rack of claim 11, wherein the removable attachment means is selected from the group consisting of screws, bolts, hook and loop type fasteners, tabs, clamps, and hinges.
14. (Currently Amended). A method of assembling a filter rack for a forced air-circulating system, the method comprising:
 - providing a plurality of longitudinal members, each longitudinal member having a first flange flanges adapted to receive and retain a filter, a second flange adapted for mounting into an air handling system, and having channels adapted to receive and retain at least one connector, each longitudinal member adapted for connection to at least one other longitudinal member to form a rectangular frame, the longitudinal members comprising comprised of a front, at least two sides, and a back;
 - providing a plurality of connectors adapted for insertion into the channels for connecting each longitudinal member to at least one other longitudinal member; and
 - connecting each longitudinal member to at least one other longitudinal member using the plurality of connectors so as to form a rectangular frame.

Application No. 10/717,825
Atty. Docket No. 20714-0028-U1

15. (Original). The method of claim 14, the method further comprising the step of:
providing a door adapted for removable attachment to at least one longitudinal member; and
attaching the door adapted to at least one longitudinal member.
16. (Original). The method of claim 14, the method further comprising the step of:
providing a door adapted for removable attachment to at least two longitudinal members; and
attaching the door to at least two longitudinal members.
17. (Currently Amended). A forced air-circulating system ~~comprising~~; ~~comprised of~~:
return air flow ducting having a rectangular cross-sectional geometry;
a filter rack connected to the return flow ducting, the filter rack comprising:
a plurality of longitudinal members having a first flange flanges adapted to receive and retain a filter, a second flange adapted for mounting into an air handling system, and having channels adapted to engage and retain a connector, the longitudinal members ~~comprise~~ ~~comprised of~~ a back member, at least two side members, and a front member, wherein the front member is configured to provide an opening to permit a filter to pass into the assembled filter rack and to be received and retained by the first flange flanges on the longitudinal members, each longitudinal member adapted for connection to at least two other longitudinal members to form a rectangular frame;
a plurality of connectors inserted into corresponding channels of individual longitudinal members for connecting each longitudinal member to at least one other longitudinal member; and
wherein the connectors are flat L-shaped connectors.
18. (Original). The forced air-circulating system of claim 17, wherein each connector further includes at least one fastener.
19. (Original). The forced air-circulating system of claim 18, wherein the at least one fastener is selected from the group consisting of bolts, screws, tabs, hook and loop type fasteners, clamps, caulking, clamps, and adhesives.

Application No. 10/717,825
Atty. Docket No. 20714-0028-U1

20. (Original). The forced air-circulating system of claim 19, wherein the filter rack is further comprised of a door that is attached to at least one longitudinal member by removable attachment means.